













Model review

		10 TYPE	11 / A TYPE	20 TYPE	21 / B TYPE	22 / C TYPE	33 / E TYPE	
B = HEIGHT (mm) D = DISTANCE BETWEEN CONNECTION CENTERS (mm)	Top view							
	Side view							
300	253	317	564	577	847	1115	1635	W
		6,22	8,53	11,97	14,28	16,84	25,14	kg
1,70		1,70	3,39	3,39	3,39	5,09	L	
1,3369		1,3459	1,3002	1,3043	1,3065	1,3162	N	
400	353	420	733	730	1067	1406	2087	W
		8,02	11,44	15,58	18,99	22,65	33,86	kg
		2,19	2,19	4,39	4,39	4,39	6,58	L
		1,3306	1,3309	1,2994	1,3142	1,3219	1,3315	N
500	453	520	890	876	1270	1681	2494	W
		9,83	14,35	19,19	23,71	28,47	42,59	kg
		2,69	2,69	5,38	5,38	5,38	8,07	L
		1,3244	1,3160	1,2986	1,3242	1,3374	1,3469	N
600	553	617	1036	1016	1460	1943	2857	W
		11,64	17,26	22,8	28,42	34,28	51,31	kg
		3,19	3,19	6,38	6,38	6,38	9,56	L
		1,3181	1,3010	1,2978	1,3341	1,3528	1,3622	N
700	653	709	1172	1151	1637	2192	3180	W
		13,44	20,16	26,41	33,13	40,10	60,03	kg
		3,68	3,68	7,37	7,37	7,37	11,05	L
		1,3118	1,3182	1,2970	1,3455	1,3620	1,3708	N
900	853	883	1413	1408	1959	2660	3715	W
		17,05	25,98	33,63	42,58	51,73	77,48	kg
		4,68	4,68	9,36	9,36	9,36	14,04	L
		1,2992	1,3526	1,2953	1,3682	1,3805	1,3881	N

Heatemission inWatts - kg = Weight- L= Water content N= Coefficient

Above data calculated per meter radiator length at 75/65/20iC in accordance with EN 442.